

TdS: Art. 0809 **SENSUAL**

Date of update 30/04/2012

Transparent matt polyurethane water-based finish, leather touch effect, enriched with special waxes.

CHARACTERISTICS:

Highly prestigious silky transparent finish, based on polyurethane resins in water with low solvent emissions, enriched with special waxes that give treated surfaces the soft textured appearance of leather. Highly water-repellent, resistant to dirt and wear. Good elasticity and adherence, washable, non-inflammable and water-based, and therefore harmless for persons and the environment.

USES:

Highly prestigious silky finish for the decoration of interior walls and ceilings in brickwork, plasterwork, concrete, mortar, plaster and similar, plasterboard, old paint, wood, hardboard, terracotta, ceramic tiles, paper, cardboard, etc.

PREPARATION AND APPLICATION:

Surfaces must be as smooth and free from defects as possible. Scrape, brush and remove old paintwork or loose plasterwork. Ensure that surfaces are solid, dry and clean. Seal any infiltrations of damp beforehand. Fill any cracks and holes and smooth surfaces with **PLASTUC A** or **STUCCO IN POLVERE MP**. Apply a first coat of **PRIMER A CONCENTRATO** diluted 1:4 with water and applied to completely saturate the surface. Apply two coats of **SETA**, a prestigious washable acrylic wall paint for interior use, or **MURALEX**, by brush, roller or airless spray, with 8 - 12 hours between coats. Dilute first coat 5 - 10% by volume with water, and 0 - 5% for the second coat. Then apply one or two coats of **SENSUAL** (according to the desired effect), ready for use. **SENSUAL is transparent, and the final colour comes from the undercoat, enhanced with a stronger shade by the presence of SENSUAL.**

Apply with fine bristle brush, acrylic brush with feathered bristles or short-haired roller.

IMPORTANT NOTES:

- Carefully mix the product before use.
- Before application, ensure that the surface is perfectly dry and hardened, and that it has good adherence to the supporting ground. It must be clean and free from oil, grease, mould, fungus, bacteria, efflorescence or any other defect that could impair adherence or successful results.
- Protect containers from freezing (minimum + 5° C).
- Store in a cool, dry place and do not expose to direct sunlight.
- Use product at a temperature of the work environment and treated surface between 8°C and 35°C. Relative humidity must not exceed 75%.
- Do not allow drying to take place with temperature of the work environment and treated surface below +5°C.
- Wash all equipment with water immediately after use.

TECHNICAL DATA:

COVERAGE	12-15 m ² /l = 0.070 - 0.080 l/m ² , according to application method.
PACKAGES	2,5 l - 1 l
STORAGE	in perfectly sealed packages away from cold, for up to 12 months and more.
COLOURS	silky transparent. "Collezione Sensual"

Emission limits of Volatile Organic Compounds (VOC) according to directive 2004/42/CE:

Classification: A/ I) "decorative effect coatings";
Limit Phase II (from 01/01/ 2010): 200 g/l
VOC: 150 g/l (max).

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

Colorificio MP S.r.l.

Mod. 51
Rev. 03
27.09.2011

Via G.Pastore, 2 Viserba 47922 - Rimini (Italy)
Tel. +39 0541 734086 Fax +39 0541 734282
mp@colorificiomp.it www.colorificiomp.it
mp@mp-paints.com www.mp-paints.com